



TRANSPORTATION CERTIFICATE

Ref. TC-MP 144350 09/03-1

This is to certify that the Saft cell type, **MP 144350**, has been subject and has met the requirements of :

- UN Recommendations on the transport of dangerous goods, Model Regulations 12th Revised edition - 2001 - Ref. ST/SG/AC.10/1/Rev. 12
- UN Recommendations on the transport of dangerous goods, Manual of Tests and Criteria 3rd Revised edition - 1999 - Ref. ST/SG/AC.10/1/Rev. 3, amended per Addendum 2, Annex 4 - Ref. ST/SG/AC.10/27/Add.2

as detailed in Saft-Poitiers internal report P 0194/03, dated 06/2003.

Concerned Part Number 06624F

Product Description

Prismatic rechargeable Lithium-ion single cell without electronic protection circuit

Nominal Voltage	3.6 Volts
Nominal Capacity	2.3 Ah
Equivalent-lithium content per cell	2.3 x 0.3 = 0.69 gram
Maximum recommended continuous discharge current	4.6 A

Product Classification

Since it passes the UN-defined transport tests and since its equivalent-lithium content does not exceed the 1.5 gram-limit, **the MP 144350 cell is declared exempt from the Dangerous Goods regulations. It is non-restricted to transport/non-assigned to Class 9**, providing packed in accordance with Clause 188 of UN Recommendations on the transport of dangerous goods, Model Regulations 12th Revised edition - 2001 - Ref. ST/SG/AC.10/1/Rev. 12.

Signed on Behalf of Saft, Specialty Battery Group

Pascal Hans SBG Product Test Engineer

dated 05/09/03

Gilles Tardivo SBG Quality Manager

dated 05/09/03

Alain Kerouanton SBG Lithium Product Manager

dated 02/09/03